

# Longo & Co

## OP138CS

### SOFT SERVE FREEZER

2+1 mixed Flavors, Floor, Digital Control  
P: Pump Feed Model



### Powerful and Versatile

Two flavor medium capacity floor model for ice cream, frozen yogurt and much more

#### Fast Freeze Down

Patented high efficiency heat exchanger allows fast freeze down with low energy consumption

#### Digital Control and Display

Microprocessor control provides access to system settings and additional functions. Digital interface displays critical info as system status, temperatures, dispense count, errors, etc.

#### Auto Programming

Allows automatic switching of operation modes based on preset schedules

#### Standby

Maintains product temperature in both mix hopper and freezing cylinder below 4.4°C (40°F) overnight

#### Hopper Agitator

Maintain product consistency and prevent product separation

Ideal for medium capacity outlets to serve ice cream, frozen yogurt, gelato or sorbet. Fully loaded with all standard options.

#### Soft System Start

Slow motor start reduces equipment noise and stress on drive train

#### Direct Drive Transmission

Eliminates consumable moving parts and increases transmission efficiency

#### Safety Protections

- Low temperature and motor overload shutoffs to protect in the event of cylinder freeze up
- High pressure switch to prevent compressor overheating

#### Quick Freeze

Turn on freeze immediately to freeze down to serving viscosity when quick service is required after long idle period

#### Self-closing Valve with Speed Control

Automatically prevents product overflow after dispense; Provides flexibility in dispense rate control





## Longo & Co

Address: Towerworks Birkhouse Lane Paddock Huddersfield HD1 4SF  
Phone: 00441484666484 Email: Info@mrwhippy.biz

# OP138CS

# SOFT SERVE FREEZER



## SPECIFICATIONS

Flavors	2+Twist
Freezing Cylinders	2X2L/2.1qt
Mix Hoppers	2X12L
Output Capacity (80 grams)	380serves/hr
Clearance Requirements	152mm/6" on back

Weight	Kg/lb (Gravity)	Kg/lb (Pump)
Net	180/397	195/430
Shipping	220/485	235/518
Volume	0.97CBM/34.25CBF	

Dimensions	Net (mm/in)	Shipping (mm/in)
Width	540/21.3	670/26.4
Depth	800/31.5	870/34.3
Height	1431/56.4	1665/65.6

Electrical	Power (kW)	Total Amps (A)	Fuse (A)
220-240/50/1	2.6	14	20
208-230/60/1	2.8	16	20

## FEATURES

Control Systems	Single, Digital
Refrigerated Hoppers	<input checked="" type="checkbox"/>
Hopper Agitators	<input checked="" type="checkbox"/>
Temperature Displays	<input checked="" type="checkbox"/>
Standby Mode	<input checked="" type="checkbox"/>
Auto Closing Dispensing Valves	<input checked="" type="checkbox"/>
Dispensing Speed Control	<input checked="" type="checkbox"/>
Low Mix Indicator Light & Alarm	<input checked="" type="checkbox"/>
Low Temperature Protection	<input checked="" type="checkbox"/>
Motor Overload Protection	<input checked="" type="checkbox"/>
High Pressure Protection	<input checked="" type="checkbox"/>
Quick Freeze	<input checked="" type="checkbox"/>
Soft Start	<input checked="" type="checkbox"/>
Direct Drive Pump (P only)	<input checked="" type="checkbox"/>

## AVAILABLE OPTIONS

Water Cooled	<input checked="" type="checkbox"/>
Top Air Discharge Chute	<input checked="" type="checkbox"/>

•Above specifications are subject to change without notice

## Longo &Co

Address: Towerworks Birkhouse Lane Paddock Huddersfield HD1 4SF  
 Phone: 00441484666484 Email: Info@mrwhippy.biz